

Mash Up is Milliken's latest product concept developed with the specific objective of reducing waste within our industry.



The idea is simple but powerful. In any textile manufacturing environment, however responsible the manufacturing processes are, there will inevitably be some 'waste'. This might be overruns, cancelled orders or unused samples and all this material is first quality. Through the Mash Up collection, this material is put to good use and Milliken clients can benefit.

## How Mash Up Works:

We've combined our excess material into useable colour palettes and like constructions to offer a collection of mixed but visually cohesive combinations that can be used creatively to create fun and contemporary patchwork layouts on the floor. The results are sometimes unexpected but always stunning! Using these palettes Milliken customers can proactively reduce waste within our industry.

## Mash Up Products:

All products included in Mash Up offer:

- Cushion backing to provide luxurious underfoot comfort and impressive acoustic credentials
- The option to add TractionBack 2.0 for adhesive free installation
- Non directional / batchless layout possibilities
- A 5 year wear warranty

## What You'll Get:

- An environmentally responsible floorcovering product that is helping to minimise waste in the industry
- A floor covering with a high performance specification that is very affordable
- First quality carpet

## What to order:

We've grouped the collections into like formats (tile or plank), consistent thicknesses and cohesive colour palettes.

1. Simply select a format – tile or plank
2. Select your backing type – WellBAC® Comfort Plus or Comfort Lite
3. Choose your colour palette
4. Place your order

50 cm Tile - Examples of Colour Palettes\* - (Available with WellBac® Comfort Plus or Comfort Lite cushion backing)



Neutrals – Beiges



Neutrals – Greys



Neutrals – Darks



Blues




Brights



Multi Coloured

\*Images shown are suggestions of the colour palettes. Actual colours / designs within each palette will always vary.

**25 x 100cm Plank** - Examples of Colour Palettes\* - (Available with WellBac® Comfort Plus or Comfort Lite cushion backing)



Multi Coloured

\*Images shown are suggestions of the colour palettes. Actual colours / designs within each palette will always vary.

---

**CUSTOMER SERVICE**

SERVICE CLIENT / KUNDENSERVICE-  
CENTER / SERVICIO AL CLIENTE

**UK**

T. +44 (0)1942 612 777  
E. carpetenquiries@milliken.com

**FRANCE**

T. 08 05 54 27 77  
E. demandesmoquettes@milliken.com

**DEUTSCHLAND**

T. 0800 7243794  
E. verkauf@milliken.com

**ESPAÑA**

T. +44 (0)1942 612 777  
E. informaciondemoqueta@milliken.com

**SHOWROOMS**

**LONDON**

T. +44 (0)20 7336 7290

5 Berry Street,  
Clerkenwell,  
London EC1V 0AA

**PARIS**

T. +33 (0)1 40 98 06 99

40 Rue Des Mathurins,  
75008 Paris

**EUROPEAN HEAD OFFICE**

SIÈGE EUROPÉEN / EUROPÄZENTRALE /  
SEDE CORPORATIVA EUROPA

T. +44 (0)1942 826 073

Beech Hill Plant,  
Gidlow Lane,  
Wigan WN6 8RN

---

**Version 1**

Issued May 2023  
Publiée mai 2023  
Ausgabe Mai 2023  
Expedida mayo 2023

[www.millikenfloors.com](http://www.millikenfloors.com)

Milliken™

# MASH UP

WellBAC® Comfort Plus - Tile



|                         |                                                                                                                      |
|-------------------------|----------------------------------------------------------------------------------------------------------------------|
| Construction            | Tufted, Textured Loop Pile                                                                                           |
| Face Fibre              | 100% Nylon                                                                                                           |
| Finished Face Weight    | 600 g/m <sup>2</sup> - 915 g/m <sup>2</sup>                                                                          |
| Gauge                   | 39.4 / 10cm and 47.2 / 10 cm                                                                                         |
| Rows                    | 39.3 - 47.2 / 10 cm                                                                                                  |
| Finished Pile Height    | 3.2 - 5.0 mm                                                                                                         |
| Standard Backing        | WellBAC® Comfort Plus 90% recycled open cell polyurethane cushion backing<br>Available with TractionBack® on request |
| Nominal Total Thickness | 9.9 - 11.4 mm                                                                                                        |
| Tile Size               | 50 cm x 50 cm                                                                                                        |
| Nominal Total Weight    | 4100 - 4700 g/m <sup>2</sup>                                                                                         |
| Tiles per Box           | 18 (4.5m <sup>2</sup> )                                                                                              |

## PERFORMANCE

|                                                  |                                          |
|--------------------------------------------------|------------------------------------------|
| Flammability (Euroclassification EN13501:1-2018) | Class Cfl - s1                           |
| Flammability (Radiant Panel ASTM-E-648)          | Class 1                                  |
| Flammability (Hot Metal Nut BS4790)              | Low Radius of Char                       |
| Use Classification (EN 1307)                     | Class 33 Heavy Commercial Use            |
| Castor Chair (BS EN 985:2001)                    | Class A - Intensive use (r value ≥ 2.4)  |
| Static Electricity (ISO 6356)                    | Pass ≤ 2.0 KV Permanent Conductive Fibre |
| Impact Sound (ISO 10140-3)                       | Minimum 33 dB ΔL <sub>w</sub>            |
| Sound Absorption (ISO354)                        | Minimum 0.30 Class D                     |

## ENVIRONMENTAL

Minimum 59% recycled content by total product weight

Manufactured in ISO14001 certified location using renewable sources

M/PACT Carbon Neutral Floors,  
Estimated average 8.27 kg CO<sub>2</sub> e/m<sup>2</sup> Embodied Carbon  
(EPD calculation A1-A3) Cradle to Gate footprint 100% off set

## WARRANTIES

5 year wear warranty

Lifetime Antistatic guarantee

Latent Defects guarantee

## CERTIFICATIONS

[www.millikenfloors.com/gb/tech](http://www.millikenfloors.com/gb/tech)

|  |  |  |  |  |  |  |  |  |  |  |  |  |
|--|--|--|--|--|--|--|--|--|--|--|--|--|
|  |  |  |  |  |  |  |  |  |  |  |  |  |
|  |  |  |  |  |  |  |  |  |  |  |  |  |

## INSTALLATION

Non-directional /  
Batchless

## CE / UKCA

|                                 |                                 |  |  |  |  |
|---------------------------------|---------------------------------|--|--|--|--|
|                                 |                                 |  |  |  |  |
| DOP-2895-1004-01<br>BS EN 14041 | DOP-0338-1004-01<br>BS EN 14041 |  |  |  |  |

# MASH UP

Comfort Lite - Tile

|                         |                                                                                                             |
|-------------------------|-------------------------------------------------------------------------------------------------------------|
| Construction            | Tufted, Textured Loop Pile                                                                                  |
| Face Fibre              | 100% Nylon                                                                                                  |
| Finished Face Weight    | 420 g/m <sup>2</sup> - 610 g/m <sup>2</sup>                                                                 |
| Gauge                   | 39.4 / 10 cm and 47.2 / 10 cm                                                                               |
| Rows                    | 37.5 - 65 / 10 cm                                                                                           |
| Finished Pile Height    | 2.2 - 3.4 mm                                                                                                |
| Standard Backing        | Comfort Lite 90% recycled open cell polyurethane cushion backing<br>Available with TractionBack® on request |
| Nominal Total Thickness | 8.1 - 9.4 mm                                                                                                |
| Tile Size               | 50 cm x 50 cm                                                                                               |
| Nominal Total Weight    | 3700 - 4100 g/m <sup>2</sup>                                                                                |
| Tiles per Box           | 20 (5m <sup>2</sup> )                                                                                       |

## PERFORMANCE

|                                                  |                                          |
|--------------------------------------------------|------------------------------------------|
| Flammability (Euroclassification EN13501:1-2018) | Class Bfl - s1                           |
| Flammability (Radiant Panel ASTM-E-648)          | Class 1                                  |
| Flammability (Hot Metal Nut BS4790)              | Low Radius of Char                       |
| Use Classification (EN 1307)                     | Class 33 Heavy Commercial Use            |
| Castor Chair (BS EN 985:2001)                    | Class A - Intensive use (r value ≥ 2.4)  |
| Static Electricity (ISO 6356)                    | Pass ≤ 2.0 KV Permanent Conductive Fibre |
| Impact Sound (ISO 10140-3)                       | Minimum 28 dB ΔL <sub>w</sub>            |
| Sound Absorption (ISO354)                        | Minimum 0.25 Class E                     |

## ENVIRONMENTAL

Minimum 59% recycled content by total product weight

Manufactured in ISO14001 certified location using renewable sources

M/PACT Carbon Neutral Floors,  
Estimated average 5.74 kg CO<sub>2</sub> e/m<sup>2</sup> Embodied Carbon  
(EPD calculation A1-A3) Cradle to Gate footprint 100% off set

## WARRANTIES

5 year wear warranty

Lifetime Antistatic guarantee


Latent Defects guarantee

## CERTIFICATIONS

[www.millikenfloors.com/gb/tech](http://www.millikenfloors.com/gb/tech)

|  |  |  |  |  |  |  |  |  |  |  |  |  |  |
|--|--|--|--|--|--|--|--|--|--|--|--|--|--|
|  |  |  |  |  |  |  |  |  |  |  |  |  |  |
|  |  |  |  |  |  |  |  |  |  |  |  |  |  |

## INSTALLATION

Non-directional /  
Batchless

## CE / UKCA

|                                 |                                 |  |  |  |  |
|---------------------------------|---------------------------------|--|--|--|--|
|                                 |                                 |  |  |  |  |
| DOP-2895-1004-02<br>BS EN 14041 | DOP-0338-1004-02<br>BS EN 14041 |  |  |  |  |

# MASH UP

WellBAC® Comfort Plus - Plank



|                         |                                                                                                                      |
|-------------------------|----------------------------------------------------------------------------------------------------------------------|
| Construction            | Tufted, Textured Loop Pile                                                                                           |
| Face Fibre              | 100% Nylon                                                                                                           |
| Finished Face Weight    | 870 g/m <sup>2</sup> - 915 g/m <sup>2</sup>                                                                          |
| Gauge                   | 39.4 / 10cm and 47.2 / 10 cm                                                                                         |
| Rows                    | 46.2 - 47.2 / 10 cm                                                                                                  |
| Finished Pile Height    | 4.3 - 4.6 mm                                                                                                         |
| Standard Backing        | WellBAC® Comfort Plus 90% recycled open cell polyurethane cushion backing<br>Available with TractionBack® on request |
| Nominal Total Thickness | 11.4 - 12.2 mm                                                                                                       |
| Plank Size              | 25 cm x 100 cm                                                                                                       |
| Nominal Total Weight    | 4600 - 4700 g/m <sup>2</sup>                                                                                         |
| Planks per Box          | 8 (2.0m <sup>2</sup> )                                                                                               |

## PERFORMANCE

|                                                  |                                          |
|--------------------------------------------------|------------------------------------------|
| Flammability (Euroclassification EN13501:1-2018) | Class Cfl - s1                           |
| Flammability (Radiant Panel ASTM-E-648)          | Class 1                                  |
| Flammability (Hot Metal Nut BS4790)              | Low Radius of Char                       |
| Use Classification (EN 1307)                     | Class 33 Heavy Commercial Use            |
| Castor Chair (BS EN 985:2001)                    | Class A - Intensive use (r value ≥ 2.4)  |
| Static Electricity (ISO 6356)                    | Pass ≤ 2.0 KV Permanent Conductive Fibre |
| Impact Sound (ISO 10140-3)                       | Minimum 33 dB ΔL <sub>w</sub>            |
| Sound Absorption (ISO354)                        | Minimum 0.30 Class D                     |

## ENVIRONMENTAL

Minimum 58% recycled content by total product weight

Manufactured in ISO14001 certified location using renewable sources

M/PACT Carbon Neutral Floors,  
Estimated average 9.73 kg CO<sub>2</sub> e/m<sup>2</sup> Embodied Carbon  
(EPD calculation A1-A3) Cradle to Gate footprint 100% off set

## WARRANTIES

5 year wear warranty

Lifetime Antistatic guarantee


Latent Defects guarantee

## CERTIFICATIONS

[www.millikenfloors.com/gb/tech](http://www.millikenfloors.com/gb/tech)

|  |  |  |  |  |  |  |  |  |  |  |  |  |  |
|--|--|--|--|--|--|--|--|--|--|--|--|--|--|
|  |  |  |  |  |  |  |  |  |  |  |  |  |  |
|  |  |  |  |  |  |  |  |  |  |  |  |  |  |

## INSTALLATION

Non-directional /  
Batchless

## CE / UKCA

|                                 |                                 |  |  |  |  |
|---------------------------------|---------------------------------|--|--|--|--|
|                                 |                                 |  |  |  |  |
| DOP-2895-1004-01<br>BS EN 14041 | DOP-0338-1004-01<br>BS EN 14041 |  |  |  |  |

# MASH UP

Comfort Lite Plank

|                         |                                                                                                             |
|-------------------------|-------------------------------------------------------------------------------------------------------------|
| Construction            | Tufted, Textured Loop Pile                                                                                  |
| Face Fibre              | 100% Nylon                                                                                                  |
| Finished Face Weight    | 490 g/m <sup>2</sup> - 560 g/m <sup>2</sup>                                                                 |
| Gauge                   | 47.2 / 10cm                                                                                                 |
| Rows                    | 37.5 - 44 / 10 cm                                                                                           |
| Finished Pile Height    | 2.5 - 2.9 mm                                                                                                |
| Standard Backing        | Comfort Lite 90% recycled open cell polyurethane cushion backing<br>Available with TractionBack® on request |
| Nominal Total Thickness | 8.3 - 8.9 mm                                                                                                |
| Plank Size              | 25 cm x 100 cm                                                                                              |
| Nominal Total Weight    | 4000 g/m <sup>2</sup>                                                                                       |
| Planks per Box          | 12 (3m <sup>2</sup> )                                                                                       |

## PERFORMANCE

|                                                  |                                          |
|--------------------------------------------------|------------------------------------------|
| Flammability (Euroclassification EN13501:1-2018) | Class Bfl - s1                           |
| Flammability (Radiant Panel ASTM-E-648)          | Class 1                                  |
| Flammability (Hot Metal Nut BS4790)              | Low Radius of Char                       |
| Use Classification (EN 1307)                     | Class 33 Heavy Commercial Use            |
| Castor Chair (BS EN 985:2001)                    | Class A - Intensive use (r value ≥ 2.4)  |
| Static Electricity (ISO 6356)                    | Pass ≤ 2.0 KV Permanent Conductive Fibre |
| Impact Sound (ISO 10140-3)                       | 31 dB ΔL <sub>w</sub>                    |
| Sound Absorption (ISO354)                        | Minimum 0.25 Class E                     |

## ENVIRONMENTAL

Minimum 60% recycled content by total product weight

Manufactured in ISO14001 certified location using renewable sources

M/PACT Carbon Neutral Floors,  
Estimated average 5.46 kg CO<sub>2</sub> e/m<sup>2</sup> Embodied Carbon  
(EPD calculation A1-A3) Cradle to Gate footprint 100% off set

## WARRANTIES

5 year wear warranty

Lifetime Antistatic guarantee


Latent Defects guarantee

## CERTIFICATIONS

[www.millikenfloors.com/gb/tech](http://www.millikenfloors.com/gb/tech)

|  |  |  |  |  |  |  |  |  |  |  |  |  |  |
|--|--|--|--|--|--|--|--|--|--|--|--|--|--|
|  |  |  |  |  |  |  |  |  |  |  |  |  |  |
|  |  |  |  |  |  |  |  |  |  |  |  |  |  |

## INSTALLATION

Non-directional /  
Batchless

## CE / UKCA

|                                 |                                 |  |  |  |  |
|---------------------------------|---------------------------------|--|--|--|--|
|                                 |                                 |  |  |  |  |
| DOP-2895-1004-02<br>BS EN 14041 | DOP-0338-1004-02<br>BS EN 14041 |  |  |  |  |